

KD KEDRA WHITE/P/12

Model: **KD KEDRA WHITE/P/12**
 Reference: **20282**
 Size: **150X320** cm
 Thickness: **12,00** mm
 Finish:
 Body Type: **PORCELAIN - GROUP Bla**

Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm ²

Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	4

Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	//
EN ISO-10545-13	Low concentrations of acids and alkalis	//
EN ISO-10545-13	Household chemicals and swimming pool salts	/

KD KEDRA WHITE/P/12

Model: **KD KEDRA WHITE/P/12**
Reference: **20282**
Size: **150X320** cm
Thickness: **12,00** mm
Finish:
Body Type: **PORCELAIN - GROUP BIa**

Chemical characteristics

EN ISO-10545-14 Stain resistance **///**

CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**