

peronda

MILA COLD/60,7X60,7/L/R

Model: **MILA COLD/60,7X60,7/L/R**
Reference: **24236** **COLD**
Size: **60,7X60,7** cm
Thickness: **10,0000** mm
Finish: **Antideslizante Lapado**
Material: **PORCELANICO - GRUPO Bla -**

Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

Dimensional characteristics

EN ISO-10545-2	Surface appearance	> 95%
EN ISO-10545-2	Curvature	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Squareness	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

Mechanical characteristics

EN ISO 10545-11	Resistance to crazing	Cumple
EN ISO 10545-12	Resistance to crazing	Cumple
EN ISO 10545-9	Thermal shock resistance	Cumple
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Bending strength	> 35 N/mm ²

Surface characteristics

EN ISO 10545-7	Visible effect at revolutions	-
EN ISO-10545-6	Visible effect at revolutions	<175 mm ³
EN-101	Scratch resistance	5

Chemical characteristics

EN ISO-10545-13	Acids & alkalis at high concentrations	UHA/UHA/UHA
EN ISO-10545-13	Acids & alkalis at low concentrations	ULA/ULA/ULA
EN ISO-10545-13	Household cleaning products	UA/UA

peronda

MILA COLD/60,7X60,7/L/R

Model: **MILA COLD/60,7X60,7/L/R**
Reference: **24236** **COLD**
Size: **60,7X60,7** cm
Thickness: **10,0000** mm
Finish: **Antideslizante Lapado**
Material: **PORCELANICO - GRUPO Bla -**

Chemical characteristics

EN ISO-10545-14	Stain resistance	5/-/5/5
-----------------	------------------	----------------

Non-slip characteristics

ANSI A137	Stain resistance	> 0,42
BS-7976-2	Stain resistance	+36
DIN-51097	Stain resistance	A+B+C
DIN-51130	Critical slip angle, shod foot on sloping ramp	R-11
UNE-ENV-12633	Critical slip angle, shod foot on sloping ramp	3

CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**

Before laying the tiles, check the shade, calibre and quality. No claims will be accepted once the tiles have been laid. Leave a tile joint of at least 0.5 mm in the case of rectified tiles and 1.5 mm for non-rectified ones. The tile colour shown in this data sheet is merely indicative and it might differ from the real tile colour. This document is purely for sales purposes and it cannot be used in any legal or administrative proceedings, in a witness statement or as documentary proof without the express permission of